



| Departures | | | | | |
|------------|--------------|-------------|----------|------|----------|
| Time | Operator | Destination | Terminal | Gate | Boarding |
| 9:00 | Airlines | PARIS | T1 | 11 | 8:40 |
| 9:15 | Airlines Air | LONDON | T1 | 21 | 9:15 |
| 9:30 | Air Line | LONDON | T1 | 26 | 9:30 |
| 9:45 | ExpAir | NEW YORK | D2 | 5 | 9:45 |
| 10:45 | AeroFlow | NEW YORK | T1 | 11 | 10:45 |
| 11:00 | AeroFlow | SYDNEY | D2 | 21 | 11:00 |
| 11:30 | Omega | VANCOUVER | D2 | 24 | 11:30 |
| 11:40 | Arrow | PARIS | T1 | 10 | 11:40 |
| 12:00 | Arrow | LONDON | T1 | 13 | 12:00 |
| 12:10 | ExLines | MOSCOW | T1 | 21 | 12:10 |
| 12:20 | AeroFlow | TOKYO | D2 | 8 | 12:20 |
| 12:30 | AeroFlow | SEOUL | T1 | 15 | 12:30 |
| 12:45 | Airlines Air | LISSABON | D2 | 13 | 12:45 |
| 12:45 | Airlines Air | AUSTIN | D2 | 21 | 12:45 |
| 12:50 | Omega | NEW DHELI | T1 | 8 | 12:50 |
| 13:00 | Omega | NEW DHELI | D2 | 15 | 13:00 |
| 13:15 | ExLines | BERLIN | D2 | 13 | 13:15 |
| 13:30 | Arrow | WARSAW | T1 | 21 | 13:30 |
| 13:40 | AeroFlow | MADRID | T1 | 8 | 13:40 |
| 13:50 | AeroFlow | TALLINN | T1 | 15 | 13:50 |
| 14:05 | ExLines | NEW YORK | T1 | 8 | 14:05 |
| 14:05 | Omega | PARIS | T1 | 15 | 14:05 |




Unleash Professional Excellence with our
DYNAMIC DISPLAYS

Key Features

Wireless Display


The CQ series has been equipped with Wi-Fi. You can transfer the screen of your PC without a connection cable.



Android 11 OS

Unlock a world of possibilities with Android OS, empowering your commercial displays to deliver dynamic content, seamless updates, and intuitive user interfaces.



-  Quad Core A55 CPU
-  Mali G31 MP2 GPU
-  4GB RAM/ 32GB ROM
-  2.4/5 GHz Wifi
-  Operate SignEdge* solution without external PC/Media Player

24/7 Operations

The use of highly durable panel materials and quality electronic components ensures dependable 24-hour operation seven days a week.



Disclaimers

*We do not guarantee operation on all devices. Connection is possible with Android version 4.2 or later. However, connection is not possible for devices that do not have the cast function.

Key Features

Useful Connections Terminal

Equipped with a wide variety of input terminals, enabling connection to a wide range of external devices.



HDMI IN
2.0x3



HDMI OUT
2.0x1



USB
Type-C X1



USB
3.0X1 | 2.0X1



RS232 X 1



LAN port

Auto Wake Up On Input

Wake up the display just by connecting the input cable with input signal. If the display is in standby mode, just connect the HDMI1, HDMI2, or PC cable with input signal, and the display will automatically turn on and detect the desired signal.



Display in
stand by condition



*Works only on HDMI 1 HDMI 2 & PC terminal signals

Instant Mobile Content Transfer

Easily broadcast your content via Chromecast and AirPlay.



Apple
Airplay



Chromecast
built-in

Multi Mode Play



USB
auto play*



Auto play
after start-up



Playlist
scheduling

Key Features

High Haze Panel

Adopts Anti-Glare treatment panel (Haze 28%) suppresses the reflected glare of outside light and lighting.

Low Haze




*30% in 98 Inch Model



* Images are simulated.

Wide-Viewing Angle Panel

There is very little change in color, compared with the VA panel, when the screen is viewed at right or left angles.



Flexible Installation

Vertical and tilt installation allows you to choose proper installation direction according to the content.



Content auto rotate in vertical and portrait orientation.



Panasonic **SIGNEDGE™** Solution

| | | | |
|--|---|--|---|
| <p>Feed Capabilities RSS and HTML feeds display real time data.</p> | <p>Content Streams Customize your layout format based on users' needs.</p> |  | <p>Videos & Live Tv Stream HD videos, play Live TV videos.</p> |
| <p>Real-time Widgets Live information on news, weather, etc.</p> | <p>Player Management Manage everything directly from the dashboard and get all the reports.</p> |  | <p>Customer Service Pan India support and assistance .</p> |
| <p>Alerts Display any alerts in real-time without any delay.</p> | <p>Content Management Manage where and when to display and for how long.</p> |  | <p>Upgrades Simultaneous push upgrades over the network.</p> |
| <p>Social Media Link Facebook, Twitter and other social media feeds.</p> | <p>Custom Announcement Variety of fonts, colours and photo options.</p> |  | <p>User Admins Authorised edit access to chosen admins.</p> |
| <p>Import Files Make use of PowerPoint, Word, PDF, Excel and other formats.</p> | <p>Share Multiple Displays Project the content on multiple displays irrespective of the location.</p> | | <p>Integration Capabilities Easy integration with any software & mobile application.</p> |
| <p>Schedule Choose your preferred time and date to display various content automatically.</p> | <p>Reports Get the organised reports about all your display status & CMS software. Display media player on/off, assigned content report, user activity report.</p> | | <p>Creator and Approver Approve your content from the approval authority before projecting it on screen.</p> |

*Optional Software



Design & Integration: Based on customer needs, an experienced team designs & integrates the system.



Installation & Maintenance: Professional installation & technical support for all hardware (display to media players) and software [CMS on Perpetual or cloud].



Cloud Management: Reducing hardware failures and saving on costs with virtual services and network backups.



Helpdesk: Let the Panasonic helpdesk create your layout, manage, schedule & publish your digital content.

Specification Sheet

| Model | | LH-43CQ1ND | LH-55CQ1ND | LH-65CQ1ND |
|--------------------------|------------------------------|--------------------------------|---------------------------|---------------------------|
| Display | Size | 109.2 cm | 139.7 cm | 165 cm |
| | Aspect Ratio | 16:9 | | |
| | Display Area (HxV)mm | 941.2(H) × 529.4(V) | 1209.6(H) × 680.4(V) | 1428.5(H) × 803.5(V) |
| | Resolution (HxV) | 3840(H)x2160(V) | | |
| | Pixel Pitch | 0.2451mm(H) × 0.2451 mm(V) | 0.315 mm(H) × 0.315 mm(V) | 0.372 mm(H) × 0.372 mm(V) |
| | Back Light Unit | DLED | | |
| | Brightness (typ) | 500 cd/m2 | | |
| | High Haze | Yes,Haze 28% | | |
| | Viewing Angle | 178° | | |
| | Display Orientation | Landscape & Portrait | | |
| | Operation Time | 7 daysx24 hours | | |
| Connectors | HDMI IN | 2 (HDMI 2.0) | | |
| | HDMI Output | 1 (HDMI Daisy chain,Up to 3*3) | | |
| | Coaxial/Optical Output | Optical*1 | | |
| | Audio Output | 1 x 3.5mm | | |
| | USB 2.0 | 1 (F/W update / Media Play) | | |
| | USB 3.0 | 1 (F/W update / Media Play) | | |
| | RS232 | 1 | | |
| | LAN(RJ45)(10M/100M/1000M)) | 1 | 2(IN/OUT) | |
| System | System Version | Android 11 | | |
| | CPU | A55*4 | | |
| | GPU | MaliG51 MP2 | | |
| | RAM | 4GB | | |
| | ROM | 32GB | | |
| | UI | 4K | | |
| Audio | Speaker Type | Built-in Speaker | | |
| | Power | 2x12W | | |
| Slot | OPS Slot | - | - | Yes, 80 Pin OPS |
| | WIFI Slot | Yes,SI07B | | |
| Mechanisms | Bezel width(T/L/R/B) mm | 9.9/9.9/9.9/9.9 | 9.9/9.9/9.9/9.9 | 15.9/15.9/15.9/15.9 |
| | Structure | Metal Frame & Metal Rear cover | | |
| | Dimension (L*W*H) mm | 964.6x552.5x71.4 | 1233x704x71mm | 1463.3x838.3x81.6 |
| | Wall-hanging Screw | M6*12mm | M6*12mm | M8*25mm |
| | VESA (Wall mounting Size) | 200*200mm | 400*200mm | 600x400mm |
| | Dimension(package) L*W*H | 1056x156x672mm | 1332x156x819mm | 1628x208x942mm |
| | Net Weight | 9.90kg | 13.40kg | 25.40kg |
| | Gross Weight | 13.85kg | 19.50kg | 33.25kg |
| Power | Power Requirements | 100-240V~ 50/60Hz | 100-240V~ 50/60Hz | |
| | Standby Power | ≤0.5W | | |
| | Overall Power(nominal power) | 110W | 150W | 165W |
| Accessories | Remote Control | 1 pcs | | |
| Environmental Conditions | Operation Temperature | 0°C - 45°C | | |
| | Operation Humidity | 10% - 90% | | |
| | Storage Temperature | -20°C -60°C | | |
| | Storage Humidity | 10% - 90% | | |
| | Altitude Below | Below 5000 meters | | |

Specification Sheet

| Model | | LH-75CQ1ND | LH-86CQ1ND | LH-98CQ1ND |
|--------------------------|------------------------------|--|--|---------------------------|
| Display | Size | 109.2 cm | 218.4 cm | 248.92 cm |
| | Aspect Ratio | 16:9 | 16:9 | |
| | Display Area (HxV)mm | 1649.6(H) × 927.9(V) | 1895(H) × 1066(V) | 1428.5(H) × 803.5(V) |
| | Resolution (HxV) | 3840(H)x2160(V) | 3840(H)x2160(V) | |
| | Pixel Pitch | 0.4296mm(H) × 0.4296 mm(V) | 0.315 mm(H) × 0.315 mm(V) | 0.372 mm(H) × 0.372 mm(V) |
| | Back Light Unit | DLED | | |
| | Brightness (typ) | 500 cd/m2 | 500 cd/m2 | 600 cd/m2 |
| | High Haze | Yes,Haze 28% | Yes,Haze 28% | Yes,Haze 30% |
| | Viewing Angle | 178° | | |
| | Display Orientation | Landscape & Portrait | | |
| | Operation Time | 7 daysx24 hours | | |
| Connectors | HDMI IN | 2 (HDMI 2.0) | 3 (HDMI 2.0) | |
| | HDMI Output | 1 (HDMI Daisy chain,Up to 3*3) | 1 (HDMI Daisy chain,Up to 3*3) | |
| | Coaxial/Optical Output | Optical*1 | Optical*1 | |
| | Audio Output | 1 x 3.5mm | | |
| | USB 2.0 | 1 (F/W update / Media Play) | 1 (F/W update / Media Play) | |
| | USB 3.0 | 1 (F/W update / Media Play) | 1 (F/W update / Media Play) | |
| | RS232 | 1 | | |
| | LAN(RJ45)(10M/100M/1000M)) | 2(IN/OUT) | | |
| System | USB Type-C | 1 (DP1.2,PD 65W,Network Sharing(100M)) | 1 (DP1.2,PD 65W,Network Sharing(100M)) | |
| | System Version | Android 11 | | |
| | CPU | A55*4 | | |
| | GPU | MaliG51 MP2 | | |
| | RAM | 4GB | | |
| | ROM | 32GB | | |
| Audio | UI | 4K | | |
| | Speaker Type | Built-in Speaker | | |
| Slot | Power | 2x12W | | |
| | OPS Slot | Yes, 80 Pin OPS | | |
| Mechanisms | WIFI Slot | Yes,SIO7B | | |
| | Bezel width(T/L/R/B) mm | 15.9/15.9/15.9/15.9 | 15.9/15.9/15.9/15.9 | 26/26/26/26 |
| | Structure | Metal Frame & Metal Rear cover | | |
| | Dimension (L*W*H) mm | 1685.6x963.7x81.6 | 1931x1102x81.6 | 2212.9x1268.4x79.4 |
| | Wall-hanging Screw | M8*25mm | | |
| | VESA (Wall mounting Size) | 800x400mm | | |
| | Dimension(package) L*W*H | 1863x225x1090mm | 2110x225x1227mm | 2360x280x1425mm |
| | Net Weight | 34.65kg | 43.15kg | 69.9kg |
| Power | Gross Weight | 48.15kg | 60.75kg | 90.3kg |
| | Power Requirements | 100-240V 50/60Hz | | |
| | Standby Power | ≤0.5W | | |
| Accessories | Overall Power(nominal power) | 235W | 335W | 340W |
| | Remote Control | 1 pcs | | |
| Environmental Conditions | Operation Temperature | 0°C - 45°C | | |
| | Operation Humidity | 10% - 90% | | |
| | Storage Temperature | -20°C - 60°C | | |
| | Storage Humidity | 10% - 90% | | |
| | Altitude Below | Below 5000 meters | | |

Panasonic CONNECT

Scan to Connect on
Whatsapp



Registered Office: Panasonic Life Solutions India Pvt. Ltd., 12th Floor, Ambience Tower, Ambience Island, NH-8, Gurgaon-122002, Haryana, India.
Ph.: +91-124-4871300, Fax: +91-124-4871333 | Website: <https://www.panasonic.com/in/> | Toll Free number: 1800 4190 373 | Service Touch points-336

CONTACT PANASONIC TEAM FOR DETAILS AND DEMONSTRATION: PI.DSG@IN.PANASONIC.COM

T&C apply. Product, images, features, specifications shown here are for representation purpose only, actual may vary. For details, visit: www.panasonic.com/in

