CAPTURE ATTENTION.
BOOST YOUR BUSINESS.

QSR | RETAIL | SHOW WINDOW | MEETING ROOMS

DISPLAYS THAT
TRANSFORM CUSTOMER EXPERIENCE

QSR
Modernizing the QSR industry with vibrant displays.

RETAIL
Elevating retail environment with captivating content.

SHOW WINDOW
Increasing store walk-in with eye-catching visuals.

MEETING ROOMS
Transform your meeting rooms and leave a lasting impression.

SEAMLESS DISPLAY SOLUTIONS
WITH A PLETHORA OF FEATURES

Elegant and feature-rich design with content management functionality suitable
for a variety of Retail/QSR/Cafes/Meeting Rooms and outlets which are aiming to fascinate and effectively
communicate with customers.

- High Brightness-500 Nits
- 24/7 Non-stop Operation
- Haze Levels of up to 28%
- Ultra Slim
- Android OS Ver.9 SOC (RAM ROM 2GB|16GB)
- Supports LAN & RS232 Control Connection
- Wireless Connectivity
- Built-in RTC
- SignEdge*
- Versatile Usage

ELEVATE YOUR BUSINESS
THROUGH IMMERSIVE EXPERIENCES

RELIABLE AND CONVENIENT

24/7 Non-stop Operation

The high-definition displays have a designed lifespan of 50,000 hours per panel, making them durable and flexible for 24/7 operation.

Built-in RTC

The built-in RTC helps the display maintain the time sync and also synchronizes the signage planograms with the server.

HIGH VISIBILITY

High Brightness- 500 Nits

Featuring a brightness of 500 cd/m2, the display delivers clear video content, while its anti-glare & high-haze surface minimizes ambient light reflection.

Haze Levels of up to 28%

Content is displayed in much higher quality and reflections are minimal, which makes it good for the eyes.

EASY CONNECTIVITY

Wireless Connectivity

Running content through a wireless connection provides seamless flexibility.

Android OS Ver.9 SOC (System on chip)

One can download and run Android-based applications that enable seamless connectivity.

SMART CONTENT MANAGEMENT

SignEdge*

With multiple SignEdge* features, the displays offer an end-to-end solution and help elevate your business.

Supports LAN & RS232 Control Connection

Controlled by LAN or RS 232C, the SL Series can configure the display into your existing control system.

SLEEK AND COMPACT DESIGN

Ultra Slim

With their ultra-slim design, the displays blend seamlessly with any surroundings, making them suitable for a wide range of installations.

Versatile Usage

A wide range of installation options is available for the displays, including landscape, horizontal, vertical, or tilted orientations.

FEATURES OF
PANASONIC SIGNEDGE *™ SOLUTION

Feed Capabilities
RSS and HTML feeds display real time data.

Content Streams
Customize your layout format based on users' needs.

Videos & Live Tv
Stream HD videos, play live TV videos.

Real-time Widgets
Live information on news, weather, etc.

Player Management
Manage everything directly from the dashboard and get all the reports.

Customer Service
Pan India support and assistance.

Alerts
Display any alerts in real-time without any delay.

Content Management
Manage where and when to display and for how long.

Upgrades
Simultaneous push upgrades over the network.

Social Media
Link Facebook, Twitter and other social media feeds.

Custom Announcement
Variety of fonts, colours and photo options.

User Admins
Authorised edit access to chosen admins.

Import Files
Make use of PowerPoint, Word, PDF, Excel and other formats.

Schedule
Choose your preferred time and date to display various content automatically.

Share Multiple Displays
Project content on multiple displays.

Reports
Get the organised reports about all your display status & CMS software. Display media player on/off, assigned content report, user activity report.

Creator and Approver
Approve your content from the approval authority before projecting it on screen.

Integration Capabilities
Easy integration with any software & mobile application.

Design & Integration
Based on customer needs, an experienced team designs & integrates the system.

Helpdesk
Let the Panasonic helpdesk create your layout, manage, schedule & publish your digital content.

Installation & Maintenance
Professional installation & technical support for all hardware [display to media players], and software [CMS on Perpetual or cloud].

Cloud Management
Reducing hardware failures and saving on costs with virtual services and network backups.

*Optional Software

PANASONIC SL SERIES SPECIFICATIONS

Model	LH-32SL5ND	LH-43SL5ND	LH-55SL5ND	LH-65SL5ND
Display Panel				
Screen Size	80 cm	109 cm	139.7 cm	165 cm
Aspect Ratio	16:9	16:9	16:9	16:9
Resolution	1920*1080 (Full HD)	3840*2160 (4K UHD)	3840*2160 (4K UHD)	3840*2160 (4K UHD)
Brightness	500cd/m2	500cd/m2	500cd/m2	500cd/m2
Display Contrast	4000:1	4000:1	4000:1	4000:1
Viewing Angle	178° (H) /178° (V)	178° (H) /178° (V)	178° (H) /178° (V)	178° (H) /178° (V)
Panel Life	≥50000H	≥50000H	≥50000H	≥50000H
Surface Haze	28%	28%	28%	28%
Hard Coating	3H	3H	3H	3H
Operating Hours	24/7 operation	24/7 operation	24/7 operation	24/7 operation
Technical Features				
CPU	Quad Core ARM Cortex- A35	Quad Core ARM Cortex- A35	Quad Core ARM Cortex- A35	Quad Core ARM Cortex- A35
GPU	ARM Mali-G31 MP2, Concurrent Multi-Core Processing	ARM Mali-G31 MP2, Concurrent Multi-Core Processing	ARM Mali-G31 MP2, Concurrent Multi-Core Processing	ARM Mali-G31 MP2, Concurrent Multi-Core Processing
RAM	2GB	2GB	2GB	2GB
ROM	8GB	16GB	16GB	16GB
Operating System Version	Android 9.0	Android 9.0	Android 9.0	Android 9.0
Built-in WIFI	2.4GHz/5GHz, 802.11 a/b/g/n/ac	2.4GHz/5GHz, 802.11 a/b/g/n/ac	2.4GHz/5GHz, 802.11 a/b/g/n/ac	2.4GHz/5GHz, 802.11 a/b/g/n/ac
Bluetooth	Bluetooth 5.0. Supports BLE and iBeacon	Bluetooth 5.0. Supports BLE and iBeacon	Bluetooth 5.0. Supports BLE and iBeacon	Bluetooth 5.0. Supports BLE and iBeacon
Antenna	Built-in WiFi / Bluetooth	Built-in WiFi / Bluetooth	Built-in WiFi / Bluetooth	Built-in WiFi / Bluetooth
USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
HDMI	HDMI 2.0 x 3	HDMI 2.0 x 3	HDMI 2.0 x 3	HDMI 2.0 x 3
Line Out	1 (3.5mm jack)	1 (3.5mm jack)	1 (3.5mm jack)	1 (3.5mm jack)
RJ45	1 x RJ45 (100/10Mbps)	1 x RJ45 (100/10Mbps)	1 x RJ45 (100/10Mbps)	1 x RJ45 (100/10Mbps)
RS232	Yes	Yes	Yes	Yes
Power Interface	1.5m pluggable power cord	1.5m pluggable power cord	1.5m pluggable power cord	1.5m pluggable power cord
Speaker	10W*2	10W*2	10W*2	10W*2
Input	100~240V@50/60Hz	100~240V@50/60Hz	100~240V@50/60Hz	100~240V@50/60Hz
Rated Power	70W	120W	140W	150W
Standby Power	≤2W	≤2W	≤2W	≤2W
RTC	Support continuous power-off clock for no less than 7 days, and the overall working life is no less than 3 years.	Support continuous power-off clock for no less than 7 days, and the overall working life is no less than 3 years.	Support continuous power-off clock for no less than 7 days, and the overall working life is no less than 3 years.	Support continuous power-off clock for no less than 7 days, and the overall working life is no less than 3 years.
Mechanical				
Net Dimensions	724.6*419.8*40mm	967.4*555.9*40mm	1239.7*712.5*38.6mm	1459.2*837.1*38.9mm
Net Weight	5.3kg	9.3kg	17.2kg	24.8kg
Gross Weight	7.3kg	12.5kg	22.3kg	34.3kg
Environmental Conditions				
Work Environment	Temperature:10ºC～40ºC, Humidity: 20%~80%,	Temperature:10ºC～40ºC, Humidity: 20%~80%,	Temperature:10ºC～40ºC, Humidity: 20%~80%,	Temperature:10ºC～40ºC, Humidity: 20%~80%,
Accessories				
Included Accessories	VESA standard wall mounted metal hanger (including screw bag), Remote controller	VESA standard wall mounted metal hanger (including screw bag), Remote controller	VESA standard wall mounted metal hanger (including screw bag), Remote controller	VESA standard wall mounted metal hanger (including screw bag), Remote controller
Certifications				
BIS	YES	YES	YES	YES

— 3 YEARS WARRANTY —

6

COMPETITIVE ADVANTAGES

High-Quality Manufacturing

Advanced Technologies

Full Range of Products & Customized Solutions

Strong R&D Capacity

Exemplary Service

Global Presence in Seven Continents

43.6397

Panasonic
CONNECT

@panasonicindia

@panasonic_india

www.panasonic.com/in, helpline@in.panasonic.com

Insist on a Panasonic Life Solutions India Pvt. Ltd. warranty card

PanasonicIn

@PanasonicIndia